



**REAL ADVANTAGE**

## Developed for demanding applications and high-accuracy.

The Fortus 360mc was designed for users with demanding applications for high accuracy prototyping and direct digital manufacturing. The system is equipped with an extrusion head and gantry that maintains tight positional accuracy and can produce parts with high tolerance. With FDM® (Fused Deposition Modeling) technology, the Fortus 360mc uses stable thermoplastics that continue to outperform nearly all competing technologies in accuracy, repeatability and strength. Powered by proven FDM technology, the Fortus 360mc manufactures Real Parts™ in production-grade thermoplastics.

The standard build envelope is 14 x 10 x 10 inches (355 x 254 x 254 mm), which can be upgraded to 16 x 14 x 16 inches (406 x 356 x 406 mm). With the upgrade comes two more material canister bays, for a total of four bays (two build material and two support material). The larger build envelope and the additional material canisters enable users to run larger build runs. When the first material canister is empty, an auto-changeover function loads the second canister and continues the build process uninterrupted allowing users to leave the machine unattended for long periods of time.



## SYSTEM SPECIFICATIONS

BASE SYSTEM CONFIGURATION			
Build Envelope (XYZ)	14 x 10 x 10 inches (355 x 254 x 254 mm)		
Material Delivery	One (1) Model material canisters 92 in <sup>3</sup> (1508 cc) One (1) Support material canisters 92 in <sup>3</sup> (1508 cc)		
UPGRADE CONFIGURATION			
Build Envelope (XYZ)	16 x 14 x 16 inches (406 x 356 x 406 mm)		
Material Delivery	Two (2) Model material canisters 92 in <sup>3</sup> (1508 cc) Two (2) Support material canisters 92 in <sup>3</sup> (1508 cc) Auto changeover between canisters		
MATERIAL OPTIONS			
Layer Thickness:	ABS-M30	PC-ABS	PC
0.013 inch (0.330 mm)	X	X	X
0.010 inch (0.254 mm)	X	X	X
0.007 inch (0.178 mm)	X	X	X
0.005 inch (0.127 mm)	X	X	
Support Structure:	Soluble	Soluble	BASS
Available Colors:	<input type="checkbox"/> Ivory <input type="checkbox"/> White <input type="checkbox"/> Black <input type="checkbox"/> Dark Grey <input type="checkbox"/> Red <input type="checkbox"/> Blue	<input checked="" type="checkbox"/> Black	<input type="checkbox"/> White
OTHER SPECIFICATIONS			
System Size	50.45 x 35.25 x 77.25 inches (1281 x 895.35 x 1962 mm)		
Achievable Accuracy	Parts are produced within an accuracy of ±.005 inch or ±.0015 inch per inch whichever is greater (±.127 mm or ±.0381 mm per mm).*		
	*Note: Accuracy is geometry dependent 95% confidence rating.		
Network Communication	10/100 base T connection. Ethernet protocol.		
Operator Attendance	Limited attendance for job start and stop required.		
Operating Environment	Maximum room temperature of 85°F (29.4°C). Maximum room dew point of 78°F (25.6°C).		
Power Requirements	230 VAC, 50/60 Hz, 3 phase, 16A/phase (20 amp dedicated circuit required)		
Regulatory Compliance	CE		
Software	All Fortus systems include Insight™ and Control Center™ job processing and management software. FDM TEAM™ software for multi-system and/or multi-user operations is sold separately. Visit <a href="http://www.fortus.com/software">www.fortus.com/software</a> for more information.		

### At the core: Advanced FDM® technology

Fortus systems are based on patented Stratasys FDM — Fused Deposition Modeling — technology. FDM is the industry's leading additive fabrication technology, and the only one that uses production grade thermoplastics, enabling the most durable parts.

Fortus systems use a wide range of thermoplastics with advanced mechanical properties so your parts can endure high heat, caustic chemicals, sterilization, and high impact applications.

### No special facilities needed

You can install a Fortus 3D Production System just about anywhere. No special venting is required because Fortus systems don't produce noxious fumes, chemicals, or waste.

### No special skills needed

Fortus 3D Production Systems are easy to operate and maintain compared to other additive fabrication systems because there are no messy powders or resins to handle and contain. They're so simple, an operator can be trained to operate a Fortus system in less than 30 minutes.

### Get your benchmark on the future of manufacturing

Fine details. Smooth surface finishes. Accuracy. Strength. The best way to see the advantages of a Fortus 3D Production System is to have your own part built on a Fortus system. Get your free part at: [www.fortus.com/benchmark](http://www.fortus.com/benchmark).

For more information about Fortus systems, materials and applications, call **888.480.3548** or visit [www.fortus.com](http://www.fortus.com)

Fortus 3D Production Systems  
Stratasys Incorporated  
7665 Commerce Way  
Eden Prairie, MN 55344  
+1 888 480 3548 (US Toll Free)  
+1 952 937 3000  
+1 952 937 0070 (Fax)  
[www.stratasys.com](http://www.stratasys.com)  
[info@stratasys.com](mailto:info@stratasys.com)

Fortus 3D Production Systems  
Stratasys GmbH  
Weismüllerstrasse 27  
60314 Frankfurt am Main  
Germany  
+49 69 420 994 30 (Tel)  
+49 69 420 994 333 (Fax)  
[www.stratasys.com](http://www.stratasys.com)  
[europe@stratasys.com](mailto:europe@stratasys.com)